





## ASSEMBLY INSTRUCTIONS

- 1. Lay the crossbar and two elbows on the ground, with the cavity facing upwards.
- 2. Insert the elbows into either side of cross bar and secure them with M10 x 50mm s/s hex head bolts, washers and spring washers.
- 3. Lay the uprights with spigot in line with the elbows with cavity facing upwards and secure them with M10 x 50 mm s/s hex head bolts, washers and spring washers.
- 4. Place the net support arm over the holes in the elbows and insert the M10 x 50mm s/s hex head bolts, washers and spring washers.
- 5. Attach the net to the cross bar and uprights while they are lying on the ground by inserting the net edge into the profile then pressing the PVC tube under the track curve.
- 6. Stand the goal upright and place it into the ground
- Tie the net cord to the net rail pins to reduce sag in the net.

GALAXY 62b SOCCER GOALS (WITHOUT GROUND BARS)

DRAWING NUMBER:

COMPONENTS
ONE PAIR of GOALS

20 M10 X 50 MM S/S HEX HEAD BOLT, WASHER & S/WASHER

Each Packing, Assembly & Installation sheet

ITEM

2 LEFT UPRIGHT WITH SPIGOT

2 CROSS BAR ELBOW - LEFT

CROSS BAR ELBOW - RIGHT
 NET SUPPORT ARM - LEFT
 NET SUPPORT ARM - RIGHT

2 RIGHT UPRIGHT WITH SPIGOT

2 8 MM PVC TUBE 5950 MM LONG 4 8 MM PVC TUBE 1820 MM LONG

NET 5.0 X 2.0 X 1.0 X 1.5 M
 GROUND SLEEVE AND CAP

QTY

2 CROSS BAR

ASSEMBLY INSTRUCTIONS

VEIGHT: ONE GOAL - - KG ONE NET - - KG

HLAT HARD

Oz Ring Pty Ltd
Trading as:
Play Hard Sports Equipment
ABN 79 066 094 559
24 Ern Harley Drive
Burleigh Heads Qld 4220
Phone: (07) 5593 4494
Fax: (07) 5593 4338
Website: www.playhardsports.com.au
Email: email@playhardsports.com.au

This Drawing Remains the property of Play Hard Sports Equipment ©