

ASSEMBLE THE SHELTER INCLUDING THE SEATING. PLACE IN THE REQUIRED POSITION. MARK THE ANCHOR HOLE POSITIONS. MOVE THE SHELTER TO DRILL THE HOLES. REPOSITION THE SHELTER AND INSERT THE SCREWS.

PLACE BACKREST

MOUNTING PLATE

HOLDER


FINS OVER THE


REMOVE TAPE AND PRESS

	PART	ITEM DESCIPTION	QTY	PACKED
	1A	LEFT END PANEL	1	
	1B	RIGHT END PANEL	1	
	2	CENTRE UPRIGHT	5	
	3	SCREEN FRAME	6	
	4	SEAT PLANK 3335 MM	2	
	5	SEAT BACKREST 3335 MM	2	
	6	SEAT END CAP	2	
	7	BACKREST END CAP	2	
BOLT KIT				
	24	M10 X 60 S/S BUTTON HEAD BOLT, M12 MUDGUARD WASHER, S/WASHER		
	14	HEX HEAD METAL SEAT SCREWS		
	14	M12 X 150 MM CONCRETE SCREWS		
	21	50 X 50 MM THICK WALL END CAPS		

THE SHELTER CONSISTS OF UPRIGHT SUPPORTS, SCREEN FRAMES AND BENCH SEATING PLANKS.

- * HOLD TWO UPRIGHT SO THE SCREEN WILL FIT BETWEEN THEM.
- * PLACE THE TWO LUGS ON THE BOTTOM OF THE SCREEN INTO THE LUGS ON EACH UPRIGHT.
- * ROTATE THE SCREEN UPWARD TILL IT FITS FLUSH WITH THE UPRIGHT.
- * INSERT TWO BOLTS, WASHERS AND SPRING WASHERS THROUGH THE SCREEN FRAME AND INTO THE UPRIGHTS.
- * AFTER THE SHELTER IS ASSEMBLED, ALIGN ALL THE UPRIGHTS USING THE SEAT AND BACKREST PLANKS.
- * REMOVE THE TAPE COVER FILM AND REINSTALL THE SEAT AND BACKREST.
- * ADJUST THE POSITION OF THE SHELTER ON THE SLAB AND MARK THE HOLE POSITIONS ON THE SLAB.
- * DRILL 12MM X 100MM ANCHOR HOLES AND BOLT THE SHELTER IN PLACE USING 12MM X 150MM CONCRETE SCREWS.





AURORA 12 PLAYER SHELTER DRAWING NUMBER: ASSEMBLY WEIGHT: 230 KG # OF PACKAGES ORDER PACKED BY:



Oz Ring Pty Ltd Trading as:

Play Hard Sports Equipment ABN 79 066 094 559

> 24 Ern Harley Drive Burleigh Heads Qld 4220

Phone: (07) 5593 4494 Fax: (07) 5593 4338

Website: www.playhardsports.com.au Email: email@playhardsports.com.au