



NET ROPE INSTRUCTION:

FRONT GATE POLE:

1. IDENTIFY ALL THE ROPES SUPPLIED. THEY SHOULD HAVE THEIR LENGTHS WRITTEN ON EACH ONE OF THEM.

21.5 M LIFTING ROPE

2. THEN, FEED THE FREE END (WITH OUT EYE) OF 21.5M LIFTING ROPE STARTING FROM GATE END AND THEN FEED IT TO THE PULLEY. AND THEN TO THE PULLEY ON THE BASE POLE.

18.5 M LIFTING ROPE

3. THEN FEED THE FREE END (WITH OUT EYE) OF THE 18.5M LIFTING ROPE TO THE ROPE WHEEL AT THE TOP OF UPPER POLE AND ONTO THE PULLEY ON THE BASE POLE.

17 M LIFTING ROPE

4. THEN FEED THE FREE END (WITH OUT EYE) OF THE 17M LIFTING ROPE TO THE ROPE WHEEL AT THE REAR EXTENSION ARM OF GATE POLE, AND THEN TO THE PULLEY AND THEN TO THE EYEBOLT

9.5 M WHITE GATE OPEN CLOSE/ROPE

5. THEN ATTACH TWO X 9.5M WHITE ROPE TO THE GATE ARM AND FEED THEM TO THE PULLEY AT THE BACK OF THE TOP POLE.

THEN REPEAT THE SAME PROCESS FOR THE OTHER GATE POLE.

REAR POLE :

18.5 M LIFTING ROPE

1. FEED THE FREE END (WITH OUT EYE) OF THE 18.5M LIFTING ROPE TO THE ROPE WHEEL AT REAR POLE EXTENSION ARM, AND THEN TO THE SINGLE PULLEY. THEN PASS IT THROUGH THE DOUBLE PULLEY AND THEN TO THE EYE BOLT.

15.5 M LIFTING ROPE

2. FEED THE FREE END (WITH OUT EYE) OF THE 15.5M LIFTING ROPE TO THE ROPE WHEEL AT THE BACK END OF REAR UPPER POLE AND ONTO THE DOUBLE PULLEY, THEN PASS IT ONTO THE SINGLE PULLEY ON TOP OF THE UPPER POLE.

REPEAT THE SAME PROCESS FOR THE OTHER SIDE.

TITLE: THOR 9 HAMMER CAGE ROPE ATTACHMENT DETAILS				
DRAWING NUMBER: THOR 9	CHECKED BY: -			
DESIGNED BY: TREVOR	DRAWN BY: UMESH			
ACOT.: m m.	DATE: 19/03/2025			
TOLERANCE: 0.0 ± 1.0 0.00 ± 0.5 0.000 ± 0.2	0.0° ± 1° 0.00° ± 0.5°	SCALE: - : -	SYSTEM:	A3
			Oz Ring Pty Ltd Trading as: Play Hard Sports Equipment ABN 79 066 094 559 24 Em Harley Drive Burleigh Heads Qld 4220 Phone: (07) 5593 4494 Fax: (07) 5593 4338 Website: www.playhardsports.com.au Email: email@playhardsports.com.au	