## **ASSEMBLY INSTRUCTIONS** 12800 (CENTRE TO CENTRE DISTANCE) **NOTE: GROUND** NOTE: TITLE: SLEEVE TO BE SET THE SLEEVE SHOULD BE SET 3MM BELOW WITH 1 DEGREE SURFACE LEVEL TO ALLOW THE LID TO SIT **OUTWARD ANGLE** FLUSH WITH THE SURFACE. **EHC75P SLEEVE SURROUND** 603 503 **TENNIS POSTS** 503 603 N20 CONCRETE **FOOTING DETAILS** FOOTING WITH EHC75p PVC SLEEVE **GROUND SLEEVE GRAVEL FOR** DRAINAGE 450 450

COMPONENTS	
QTY	ITEM
2	SLEEVE SURROUND WITH HINGED LID
2	500 MM LONG 110 OD PVC SLEEVE
-	-
-	-
-	-
-	-
-	-
-	-
-	-
-	-
-	-
-	-
-	-
-	-

## EHC75p PVC SLEEVE WITH HINGED COVER

DRAWING NUMBER:

EHC75p ASSEMBLY

WEIGHT:

CUBIC MEASURE



Oz Ring Pty Ltd Trading as:

Play Hard Sports Equipment ABN 79 066 094 559

24 Ern Harley Drive

Burleigh Heads Qld 4220 Phone: (07) 5593 4494

Fax: (07) 5593 4338

Website: www.playhardsports.com.au Email: email@playhardsports.com.au